



OTÁČKY RPM	MODEL MODEL	PRŮTOK FLOW		TLAK PRESSURE		VÝKON POWER		HMOTNOST WEIGHT	
		l/min	GPM	bar	PSI	HP	kW		
1450	MC 13/20 S	13.0	3.4	200	3000	6.7	4.9	9.1	S = Vnější hřídel 24 mm S = Male Shaft 24 mm
	MC 13/20 I	13.0	3.4	200	3000	6.7	4.9	9.6	
	MC 15/15 S	15.0	4.0	150	2200	5.8	4.2	9.1	I = Dutý hřídel 28 mm (s přírubou M02) I = Hollow Shaft 28 mm (with Flange M02)
	MC 15/20 S	15.0	4.0	200	3000	7.7	5.7	9.1	
	MC 16/20 I	16.0	4.2	200	3000	8.2	6.0	9.6	
	MC 18/20 S	18.0	4.8	200	3000	9.2	6.8	9.1	
	MC 20/15 S	20.0	5.3	150	2200	7.7	5.7	9.1	
	MC 20/20 S	20.0	5.3	200	3000	10.3	7.5	9.1	
1750	MD 4.0/20 S	15.0	4.0	140	2000	5.4	4.0	9.1	S = Vnější hřídel 24 mm S = Male Shaft 24 mm
	MD 4.0/20 U	15.0	4.0	140	2000	5.4	4.0	9.8	
	MD 4.0/30 S	15.0	4.0	200	3000	7.7	5.7	9.1	U = Dutý hřídel 1"1/8 (s přírubou M03) U = Hollow Shaft 1"1/8 (with Flange M03)
	MD 4.0/30 U	15.0	4.0	200	3000	7.7	5.7	9.8	
	MD 5.0/30 S	19.0	5.0	200	3000	9.7	7.2	9.1	
	MD 5.0/30 U	19.0	5.0	200	3000	9.7	7.2	9.8	
2800	ME 15/20 S	15.0	4.0	200	3000	7.7	5.7	9.1	S = Vnější hřídel 24 mm/Male Shaft 24 mm
3400	ML 3.5/30 W	13.2	3.5	200	3000	6.7	4.9	10.0	W = Dutý hřídel 1" (s přírubou M01) W = Hollow Shaft 1" (with Flange M01)
	ML 4.0/30 W	15.0	4.0	200	3000	7.7	5.7	10.0	
	ML 5.0/30 W	19.0	5.0	200	3000	9.7	7.2	10.0	

Rozměrový náčrt se nachází na další straně.
For overall dimensions see page beside.

Viz str. 35-36 / See page 35-36